

BK250A


Old Product Number: HHR250A

Nickel Metal Hydride Battery [N: Standard]


Dimensions



Typical charge characteristics



Typical discharge characteristics



Specifications

Diameter		17.0 +0.0 / -0.7 mm	
Height		50.0 +0.0 / -2.0 mm	
Approximate Weight		37 g	
Nominal Voltage		1.2 V	
Discharge Capacity ^{*1}	Average ^{*2}	2600 mAh	
	Rated (min.)	2450 mAh	
Approx. Internal impedance at 1000Hz at charged state.		20 mΩ	
Charge	Standard	245 mA X 16 hrs.	
	Rapid ^{*3}	1225 mA X 2.4 hrs.	
Ambient Temperature	Charge	Standard	0 °C to 45 °C
		Rapid	0 °C to 40 °C
	Discharge		-30 °C to 65 °C
	Storage	<1 year	-30 °C to 35 °C
		<6 months	-30 °C to 45 °C
		<1 month	-30 °C to 55 °C

*1 After charging at 0.1 It for 16 hours, discharging at 0.2 It.

*2 For reference only.

*3 Need specially designed control system. Please contact Panasonic Energy for details.

Attention

Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic Energy when determining charge/discharge specs, warning label contents and unit design.

Panasonic Energy Co., Ltd.

<https://industrial.panasonic.com/ww/products/pt/nickel-metal>

As of July, 2023. This data in this document is for descriptive purposes only and is not intended to make or imply any guarantee or warranty. The contents of this product information are subject to change without notice.

