

# 2S1P MP174565xtd


## RECHARGEABLE LI-ION BATTERY



Picture for reference only

This Li-Ion battery uses a MP174565xtd cell which is ideally suited for applications requiring high energy, long operating life under cycling conditions and offers excellent performance in harsh environments.

### ❖ KEY FEATURES

- Cycle life more than 1800 cycles at 100% DoD at C/2 discharge rate and 1C charge rate
- Stainless steel cell casing
- No memory effects
- Manufactured in France 

### ❖ WARNING

- Do not crush, short-circuit, incinerate, dismantle, immerse in any liquid, heat above +60°C
- Observe charging conditions
- Refer to Li-ion Battery User manual for further information on the use.

### ❖ INFORMATIONS

- Information in this document is subject to change without notice and becomes contractual only after written confirmation by WILLIAMSON ELECTRONIQUE.

## SPECIFICATIONS

Designation	2S1P MP174565xtd SG
Part number	<b>WILPA7202</b>
Battery type	RECHARGEABLE
Technology	Li-ion
Cell manufacturer	SAFT
Homologation	UN38.3

## ELECTRICAL CHARACTERISTICS

Nominal voltage	7.3 V
Typical capacity (at C/5 rate, +25°C, 2.5V cut-off)	4 Ah
Nominal energy	29.2 Wh
Recommended max. discharge current*	5 A to 5.4 V
Charging method	Constant Current/Constant Voltage
Charging voltage	8.4 V $\pm$ 0.08 V
Max. charge current*	4 A
Storage & transportation temperatures*	+10 °C to +30 °C
Operating temperatures*	Charge -30 °C to +85 °C Discharge -40 °C to +85 °C

\*For more severe conditions contact Williamson Electronique

## PHYSICAL CHARACTERISTICS

Length**	46 mm
Width**	36 mm
Height**	70 mm
Weight**	210 g
Wires gauge	20 AWG
Wires length**	200 mm
Connector	N/A
Polarity	Plus: Red / Minus: Black
Casing	Heat-shrinkable Sleeve

\*\*For reference only.